

# SPECIFICATIONS

## RIDING TRACTORS

### 8183-T

**Engine:** Onan, opposed 2-cylinder, four cycle, air cooled.

**Horsepower:** 18 HP at 3600 RPM.

**Fuel System:** Automotive type, diaphragm fuel pump.

**Starting System:** Automotive Bendix gear starter for positive start, 12 Volt system, Key ignition with Safety Interlock.

**Air Cleaner:** Carburetor mounted dry type with replaceable element.

**Oil Capacity:** (Engine) 4 Pints, (Transmission) 6 Quarts.

**Fuel Capacity:** 5.3 U.S. Gallons.

**Lubrication System:** (Engine) Force feed oil pump.

**Transmission:** All-gear. **Speeds:** Eight, reverse in any forward gear.

**Speed Range:** 0.5-8.54 MPH.

**Attachment Power Take-Off:** Positive all-gear and friction clutch drive with safety interlock.

**Tires:** (Pneumatic) Front — 16 x 6.50-8 Lawn & Garden tread. Rear — 23 x 8.50-12 Lawn & Garden tread.

**Turning Radius:** (Equal right & left) 8' (Inside) 3.6'.

**Shipping Weight:** (approximate) 880 pounds.

**Length:** 81.5"

**Width:** 41.75"

**Height:** 43"

**Hydraulic Lift:** Standard.

**Headlights:** Standard.

### 8162-T/8163-T

**Engine:** Onan, opposed 2-cylinder, four cycle, air cooled.

**Horsepower:** 16 HP at 3600 RPM.

**Fuel System:** Automotive type, diaphragm fuel pump.

**Starting System:** Automotive Bendix gear starter for positive start, 12 Volt system, Key ignition with Safety Interlock.

**Air Cleaner:** Carburetor mounted dry type with replaceable element.

**Oil Capacity:** (Engine) 4 Pints, (Transmission) 6 Quarts.

**Fuel Capacity:** 5.3 U.S. Gallons.

**Lubrication System:** (Engine) Force feed oil pump.

**Transmission:** All-gear. **Speeds:** Eight, reverse in any forward gear.

**Speed Range:** 0.5-8.54 MPH.

**Attachment Power Take-Off:** Positive all-gear and friction clutch drive with safety interlock.

**Tires:** (Pneumatic) Front — 16 x 6.50-8 Lawn & Garden tread. Rear — 23 x 8.50-12 Lawn & Garden tread.

**Turning Radius:** (Equal right & left) 8' (Inside) 3.6'.

**Shipping Weight:** (approximate) 880 pounds.

**Length:** 81.5"

**Width:** 41.75"

**Height:** 43"

8162-T: Manual attachment lift.

8163-T: Hydraulic attachment lift.

**Headlights:** Standard.

### 8122/8123

**Engine:** Kohler single cylinder, four cycle, air cooled, automatic compression release.

**Horsepower:** 12 HP at 3600 RPM.

**Fuel System:** Automotive type, diaphragm fuel pump.

**Starting System:** Automotive Bendix gear starter for positive start, 12 Volt system, Key ignition with Safety Interlock.

**Air Cleaner:** Carburetor mounted dry type with replaceable element.

**Oil Capacity:** (Engine) 4 Pints, (Transmission) 6 Quarts.

**Fuel Capacity:** 5.3 U.S. Gallons.

**Lubrication System:** (Engine) Splash.

**Transmission:** All-gear. **Speeds:** Eight, reverse in any forward gear.

**Speed Range:** 0.5-8.54 MPH.

**Attachment Power Take-Off:** Positive all-gear and friction clutch drive with safety interlock.

**Tires:** (Pneumatic) Front — 16 x 6.50-8 Lawn & Garden tread. Rear — 23 x 8.50-12 Lawn & Garden tread.

**Turning Radius:** (Equal right & left) 8' (Inside) 3.6'.

**Shipping Weight:** (approximate) 900 pounds.

**Length:** 75.5"

**Width:** 36.25"

**Height:** 43"

8122: Manual attachment lift.

8123: Hydraulic attachment lift.

**Headlights:** Standard.

### 8102

**Engine:** Kohler single cylinder, four cycle, air cooled, automatic compression release.

**Horsepower:** 10 HP at 3600 RPM.

**Fuel System:** Automotive type, diaphragm fuel pump.

**Starting System:** 12 Volt system, Key ignition with Safety Interlock.

**Air Cleaner:** Carburetor mounted dry type with replaceable element.

**Oil Capacity:** (Engine) 4 Pints, (Transmission) 6 Quarts.

**Fuel Capacity:** 5.3 U.S. Gallons.

**Lubrication System:** (Engine) Splash.

**Transmission:** All-gear. **Speeds:** Eight, reverse in any forward gear.

**Speed Range:** 0.5-8.54 MPH.

**Attachment Power Take-Off:** Positive all-gear and friction clutch drive with safety interlock.

**Tires:** (Pneumatic) Front — 16 x 6.50-8 Lawn & Garden tread. Rear — 23 x 8.50-12 Lawn & Garden tread.

**Turning Radius:** (Equal right & left) 8' (Inside) 3.6'.

**Shipping Weight:** (approximate) 880 pounds.

**Length:** 75.5"

**Width:** 36.25"

**Height:** 43"

**Lift:** Manual.

**Headlights:** Not available.

## CONVERTIBLE TRACTORS

### 5660

**Engine:** (Cast iron) 12 HP, Kohler K301, single cylinder, four cycle, air cooled, automatic compression release.

**Air Cleaner:** Carburetor mounted, dry type, replaceable element. (Optional console mounted, heavy/duty dry type, washable/replacement element.)

**Fuel System:** Automotive type, diaphragm fuel pump.

**Fuel Capacity:** 2 U.S. Gallons.

**Starting System:** 12 Volt electrical system 3 ampere charging system.

**Lubrication:** (type) Splash.

**Oil Capacity:** (Engine) 4 U.S. Pints, (Transmission) 5 U.S. Quarts.

**Transmission:** All-gear planetary trans-axle with fully enclosed P.T.O.

**Attachment P.T.O.:** All-gear drive.

**Speeds:** 4 forward, 4 reverse.

**Speed Range:** 0-4 MPH.

**Tire Options:** 18 x 6.50 x 8 Lawn & Garden tread. 4.00 x 8 Diamond tread. 4.00 x 8 Sure Grip. 18 x 8.50 x 8 Lawn & Garden tread. 16 x 5w x 3 Semi-Pneumatic/Ground Grip.

**Weight:** (approximate) 500 pounds.

**Dimensions:** (approximate) L 56" x W 26" x H 37".

### 5460

**Engine:** (Cast iron) 10 HP, Kohler K241, single cylinder, four cycle, air cooled, automatic compression release.

**Air Cleaner:** Carburetor mounted, dry type, replaceable element. (Optional console mounted, heavy/duty dry type, washable/replacement element.)

**Fuel System:** Automotive type, diaphragm fuel pump.

**Fuel Capacity:** 2 U.S. Gallons.

**Starting System:** 12 Volt electrical system 3 ampere charging system.

**Lubrication:** (Type) Splash.

**Oil Capacity:** (Engine) 4 U.S. Pints, (Transmission) 5 U.S. Quarts.

**Transmission:** All-gear planetary trans-axle with fully enclosed P.T.O.

**Attachment P.T.O.:** All-gear drive.

**Speeds:** 4 forward, 4 reverse.

**Speed Range:** 0-4 MPH.

**Tire Options:** 18 x 6.50 x 8 Lawn & Garden Tread. 4.00 x 8 Diamond tread. 4.00 x 8 Sure Grip. 18 x 8.50 x 8 Lawn & Garden tread. 16 x 5w x 3 Semi-Pneumatic/Ground Grip.

**Weight:** (approximate) 500 pounds.

**Dimensions:** (approximate) L 56" x W 26" x H 37".

### 5260

**Engine:** (Cast Iron) 8 HP, Kohler K181T, single cylinder, four cycle, air cooled, automatic compression release.

**Air Cleaner:** Carburetor mounted, dry type, replaceable element. (Optional console mounted, heavy/duty dry type, washable/replacement element.)

**Fuel System:** Automotive type, diaphragm fuel pump.

**Fuel Capacity:** 2 U.S. Gallons.

**Starting System:** 12 Volt electrical system 3 ampere charging system.

**Lubrication:** (type) Splash.

**Oil Capacity:** (Engine) 2-1/2 U.S. Pints, (Transmission) 5 U.S. Quarts.

**Transmission:** All-gear planetary trans-axle with fully enclosed P.T.O.

**Attachment P.T.O.:** All-gear drive.

**Speeds:** 4 forward, 4 reverse.

**Speed Range:** 0-4 MPH.

**Tire Options:** 18 x 6.50 x 8 Lawn & Garden tread. 4.00 x 8 Diamond tread. 4.00 x 8 Sure Grip. 18 x 8.50 x 8 Lawn & Garden tread. 16 x 5w x 3 Semi-Pneumatic/Ground Grip.

**Weight:** (approximate) 435 pounds.

**Dimensions:** (approximate) L 58" x W 25" x H 36.5".

### 5240

**Engine:** (Cast Iron) 8 HP, Kohler K181T, single cylinder, four cycle, air cooled, automatic compression release.

**Air Cleaner:** Carburetor mounted, dry type, replaceable element. (Optional console mounted, heavy/duty dry type, washable/replacement element.)

**Fuel System:** Automotive type, diaphragm fuel pump.

**Fuel Capacity:** 9/10 U.S. Gallons.

**Starting System:** Recoil start.

**Lubrication:** (type) Splash.

**Oil Capacity:** (Engine) 2-1/2 U.S. Pints, (Transmission) 5 U.S. Quarts.

**Transmission:** All-gear planetary trans-axle with fully enclosed P.T.O.

**Attachment P.T.O.:** All-gear drive.

**Speeds:** 4 forward, 4 reverse.

**Speed Range:** 0-4 MPH.

**Tire Options:** 18 x 6.50 x 8 Lawn & Garden tread. 4.00 x 8 Diamond tread. 4.00 x 8 Sure Grip. 18 x 8.50 x 8 Lawn & Garden tread. 16 x 5w x 3 Semi-Pneumatic/Ground Grip.

**Weight:** (approximate) 420 pounds.

**Dimensions:** (approximate) L 58" x W 25" x H 36.5".

### 5200

**Engine:** (Cast Iron) 8 HP, Kohler K181T, single cylinder, four cycle, air cooled, automatic compression release.

**Air Cleaner:** Carburetor mounted, dry type, replaceable element. (Optional console mounted, heavy/duty dry type, washable/replacement element.)

**Fuel System:** Automotive type, diaphragm fuel pump.

**Fuel Capacity:** 9/10 U.S. Gallons.

**Starting System:** Recoil start.

**Lubrication:** (type) Splash.

**Oil Capacity:** (Engine) 2-1/2 U.S. Pints, (Transmission) 5 U.S. Quarts.

**Transmission:** All-gear planetary trans-axle with fully enclosed P.T.O.

**Attachment P.T.O.:** All-gear drive.

**Speeds:** 2 forward, 2 reverse.

**Speed Range:** 0-2.8 MPH.

**Tire Options:** 18 x 6.50 x 8 Lawn & Garden tread. 4.00 x 8 Diamond tread. 4.00 x 8 Sure Grip. 18 x 8.50 x 8 Lawn & Garden tread. 16 x 5w x 3 Semi-Pneumatic/Ground Grip.

**Weight:** (approximate) 355 pounds.

**Dimensions:** (approximate) L 58" x W 25" x H 36.5".